



Voltige +

EL-723

COMMERCIAL ELEVATOR

Developed to meet your needs for access to all floors in a building, the Voltige+ elevator is equipped with reliable technology and is easy to maintain. Voltige+ can be installed in both new and existing buildings. This passenger elevator is designed for 2- to 5-floor buildings, such as condos, rental properties, or commercial facilities.

Whether you are an architect, a general contractor or a real estate developer, the Voltige+ is a reliable elevator that works in a variety of projects.

To facilitate your travels!



 **OPLIFT**
vertical mobility

info@oplift.ca | www.oplift.ca | 1 800 311-9977 | 450 773-9977
6555 Choquette Avenue, Saint-Hyacinthe, Québec J2S 8L2

Voltige+

EL-723

PRODUCT BROCHURE



Device type

Elevator / Commercial

Model

EL-723

Commercial name

Voltige+

MAIN SPECIFICATIONS

Applicable norms

CSA-B44-07 • ASME A17.1

Course / Trajectory

Maximum 50' (15.24 m). Calculated from the lower floor to the top floor

Capacity / Rated load

Maximum 2500 lb (1134 kg)


CABIN

Cabin dimensions

Maximum 25'2 (2.32 m2) . Possibility of various sizes.
Maximum 54" X 80" (1 372 mm X 2032 mm)

Dimensions on request

Possible configurations



Front
opening



Front and
back opening
(face to face)

Cabin panels walls

Fire proof laminate (Choice of available colours) Options: Stainless steel - Mirror panels

Architect's special requests are possible.

Handrails

Stainless steel **Special request are possible.**

CONTROL BUTTONS

Control panel and push buttons

CABIN

Brushed stainless steel control panel; Arrival indicator on floors (gong); Stainless steel square push buttons with constant pressure push button (direct action); Open-door/Close-door buttons; On floors Open-door/Close-door buttons; Emergency light on the deck - Audible alarm; Emergency phone; All inscriptions in braille for the blind; Visual position indicator
Options: Card reader, Service cabinet

FLOORS

Cabin call, up and down; Maintenance access switch; Visual position indicator
Option: Card reader

Telecommunication

Emergency communication Rath SmartPhone 6

DOORS

Landing and cabin doors

LANDING DOORS AND CABIN DOORS

Two-speed automatic sliding doors, stainless steel #4 finish or beige painted steel
Net opening: 36" (914 mm) X 84 5/8" (2149.475 mm)
Net opening: 42" (1067 mm) X 84 5/8" (2149 mm)

DRIVE MACHINE

Driving system

Hydraulic cable

Movement speed

Maximum 100'/min. (0.5 m/second). Soft start and stop. Option : 50'/min. (0,25 m/sec.)